THE ORIGINAL

SAFETEST DI SERIES

- Wireless Dial Indicator (DI)
- Available in 1,2 and 4 Channel Kits
- 50m (164ft) Bluetooth Range
- Eliminates Live Work (ELW)
- Test Multiple Channels Simultaneously
- 10 Hour Battery Life







Maximise Safety



Eliminate Live Work



Wireless up to 50m



Purpose Built for Heavy Industry



Capable of measuring up to 10mm (0.39inch) of displacement with an accuracy of 0.01mm (0.0004inch) and wireless connectivity of up to 50m (164ft) away, the SafeTest DI Series is recognised as a new industry standard.

Packaged in a rugged hard shell carry case, with built-in charging harness, the SafeTest DI Kit is always ready to go at a moment's notice. "The SafeGauge products are a great addition to our tooling inventory.

SafeGauge Dial Indicators remove personnel from the footprint of the machine - away from crush/pinch points. The DI2 Kit allows multiple tests/channels to be carried out at the same time, reducing testing duration."

Hastings Deering















SafeTest DI2 Kit

Standard DI Kit Sizes

- 1 Channel
- · 2 Channel
- · 4 Channel

Custom kits and accessories are available on request.



SafeTest Field Service Kit, also featuring the SafeTest Pressure Transducer (PT Series)

Multi-Award Winning Engineering and Design















SafeGauge's hand-held MultiTool allows technicians to monitor and record multiple channels simultaneously delivering significant productivity gains.







